

AMERICAN ONSITE PRODUCTS

BIOLINE FITTINGS



TLCOUP
Insert Coupling



TLELL
Insert Elbow



TLTEE
Insert Tee



TLCROS
Insert Cross



TL050MA
1/2" Male Adapter



TL075MA
3/4" Male Adapter



TL075FTEE
Combination Tee
Ins x Ins x 3/4" FPT



TL2W075MA
2-Way Insert
3/4" MPT x Insert



TLIAPE-B
Insert Adapter for 1" or
Larger PE (Requires 11mm
or 7/16" drill or punch)



TLIAPVC-B
Insert Adapter with Grommet
1 1/2" or larger PVC Pipe



TDBIT16.5
Drill Bit for TLIAPVC
Fitting (16.5mm or 21/32")



TLDPLUG
Dripper Plug Ring to Close Off
Individual Dripper



TLFIG8
Figure 8 Line End



TLS6
6" Soil Staple



TLSOV
Shut-Off Valve
Ins x Ins



TLCV
Inline Check Valve

- Flow Range: 0.9 to 4.4 GPM
- Opening Pressure: 7.1 psi
- Closing Pressure: 5.7 psi

Fittings Definitions

FPT = Female Pipe Thread

MPT = Male Pipe Thread

Ins x Ins = Insert by Insert

Applications

- Fits Bioline Dripperline

Features/Benefits

- Barbed fittings for secure fit
- Easy installation without glue or tools
- Maximum recommended system pressure without clamps - 50 psi
- Allows for easy on-site inspection of proper fitting installation